Warning:

- 1-Ride-on car is designed for children from 12-36 months of age. Rider's weight must not exceed 27kgs.(60lbs) as there is insufficient strength to support overweight.
- 2-Product is designed to seat 1 child as a time to avoid injuries.
- 3-Parental guidance and supervision are strongly advised to ensure safe riding.
- 4-Adult assembly and installation of all parts are required to ensure safety.
- 5-Batteries to be handled by adults.
- 6-Take care of riding and avoid going near streets.crossroads,all traffic areas, swimming pools, and stairs.
- 7-Without regular check of the product, it will cause overturn or fall
- 8-Check to see occasionally that the nut and bolt on the steering wheel is tight and secure.
- 9-Dangers may present if the product is not correctly assembled.
- 10-Shoes must be worn in use.

Battery Handling:

- 1-Battery must be handled by adults only.
- 2-Always remove exhausted batteries.
- 3-Use AA size batteries only.
- 4-Alkaline batteries are recommended.
- 5-Always remove batteries when the unit is not going to be used for an extended period of time.
- 6-When replacing new batteries, always replace all batteries.
- 7-Do not mix old and new batteries.
- 8-Do not mix Alkaline, Standard (Carbon-Zinc), or Rechargeable (Nickel-Cadmium) batteries.
- 9-Do not dispose of batteries in fire, batteries may explode or leak.

Bandits and Angels @12-3



Item No:605

Activity Ride-On

Instructions Manual



igarLown CAUTION:

IMP: Dutch Bandits B. V., Jansstraat 69, 2011 RV HAARLEM www. dutchbandits.com

INSTRUCTIONS

<Picture1>

ASSEMBLY INSTRUCTIONS

How to assemble the wheels.

- -Insert the axis through the wheels and the body, tighten by a cotter pin.
- -Assemble the two wheel caps.

How to assemble the anti-tumble shelf.


- -Place the anti-tumble shelf into the rear of the body.
- -Assemble the two screws by a screwdriver.

How to assemble the steering wheel.

- -Insert the fork post through the hole of the body.
- -Place the steering wheel over the fork post.
- -Insert the bolt into the hole and tighten with a screwdriver.

How to assemble the toddler bar

- -Place the toddler bar over the holes in the rear of the body.
- -While holding the front of the vehicle down one hand push firmly down on the toddler bar to seat the toddler bar into the holes. Be certain the toddler bar is completely seated.



How to exchange the battery.

- -Loosen the screws with a screwdriver. Keep the screw in a safe place away from children's reach.
- -Put 3 AA batteries in the battery house.
- -Then tight the screw with a screwdriver.